



Technical Data - Ignition System MKZ 100 - ( Part No. 0 096 600 017 )

Operating Voltage	:	230 V ( -15 % + 10% ) 50/60 Hz
Primary Current	:	0.22 A
Output	:	50 VA
Connections		
Primary	:	2 x flat plug 2.8 mm
Secondary	:	2 x 4 mm drop-in pins
Ignition Voltage	:	2 x 7.5 kV
Ignition Frequency	:	25 / 30 Hz
Ignition Spark Energy	:	approx. 500 mJ
Duty Cycle	:	100 %
Sparking distance	:	1.5 - 3mm
Operating temperature	:	0-60 °C
Fitting position	:	as required
Weight	:	300 g

-----  
| [BURNER / SEQUENCE CONTROLLERS \( For Big Size Burners \)](#) |  
| [UV SENSOR AND AMPLIFIERS](#) | [FLAME ROD AMPLIFIER](#) |  
| [BURNER CONTROLLERS \( For small and medium sized industries \)](#) |  
| [FLAME SENSORS](#) | [FLAME AMPLIFIER](#) | [IGNITION TRANSFORMER](#) |  
-----

| [Home](#) | [Products](#) | [Profile](#) | [Clients](#) | [Contact us](#) | [Feedback](#) |

[◀ Back](#)

[Next ▶](#)



**CONTACT DETAILS :-**

307, Vikrant Industrial Estate, Govandi Post Office Road,  
Deonar, Mumbai - 400 088, Maharashtra, India

**Tel. :** 2551 25 34

**Telefax :** (022) 2557 60 02

**Email :** [response@burnercontroller.com](mailto:response@burnercontroller.com)

**Website :** [www.linearsystem.net](http://www.linearsystem.net) , [www.uvdetector.ne](http://www.uvdetector.ne)

Designed & Hosted by : MID Promoted by : GID